



Professional FM Transceiver

Specification :

- 16 Channels
- Voice Channel Annunciation
- High/low Power Switchable
- 50 Ctcss/104 Cdcss Encode & Decode
- Auto Battery Save
- Low Battery Alert
- Busy Channel Lockout
- Time-out Timer (to)
- Emergency Alarm

General Specification	
Frequency Range	350 MHz
Channel Capacity	16
Operating Voltage	7.4V LI-ION
Working Temperature	-20°C – +60°C
Frequency Stability	± 2.5ppm
Dimensions (LxWxH)	100x55.5x31 mm
Weight	200g
Transmitter	
Power output	4W / 1W
Modulation Type	F3E
Spurious Radiation	< -60dB
Adjacent Channel Power	> 65dB
Modulation Limitation	± 5KHz
Modulation Distortion	≤ 5%
Signal Noise	40dB
Modulation Function	± 3dB
Receiver	
Sensitivity	< 0.20μV
Adjacent Channel Sensitivity	65dB
Spurious Response Rejection	65dB
Audio Power	500mW
Audio Distortion	≤5%

Standard Accessories



Battery



Belt Clip



Adapter



Antenna



Charger



Hand Strap

Optional Accessories



Program Cable



Earpiece
Microphone



Throat Mic
Earphone



Authorized Dealer: